

## PUSH-IN TYPE MALE CONNECTORS AND 90° MALE ELBOWS TYPE



### CHARACTERISTICS



- MATERIAL: BRASS
- TUBE: NYLON, RILSAN, POLYAMIDE, POLYETHYLENE, POLYURETHAN
- DIAMETERS: Ø 4 - Ø 6
- FLUID: OIL, GREASE
- WORKING TEMPERATURE : -10°C ÷ +80°C (+14°F ÷ +176°F)

The new *Dropsa High Pressure Push-in Fittings* for oil and grease offer key benefits:

- Lower part cost when compared to existing compression fittings
- Fast clamping of tube into fitting drastically reduces assembly time
- Reduced Maintenance cost from quick substitution

The *Dropsa High Pressure Push-in Fittings* are available in different types. Easily assembled and disassembled; there is no wear or damage to the tubes as previously experienced with conventional & push-in fittings.

		Max Pressure	Thread	Part Number		
	<b>STRAIGHT</b> Ø 4 Tube	65 bar 943 psi	M 6 x 1	3084579	<input type="radio"/>	_____
			M 6 x 0,75	3084631	<input type="radio"/>	_____
			1/8 BSP	3084577	<input type="radio"/>	_____
			5/16 – 24 UNF	3084682	<input type="radio"/>	_____
			M 6 x 1	3084685	<input type="radio"/>	_____
	<b>STRAIGHT</b> Ø 6 Tube	65 bar 943 psi	1/8 NPT	3084587	<input type="radio"/>	_____
			1/8 BSP	3084578	<input type="radio"/>	_____
			1/4 BSP	3084609	<input type="radio"/>	_____
			M 6 x 1	3084753	<input type="radio"/>	_____
			1/8 BSP	3084565	<input type="radio"/>	_____
			1/4 BSP	3084700	<input type="radio"/>	_____

		Max Pressure	Thread	Part Number		
	<b>90°</b> Ø 4 Tube	65 bar 943 psi	M 6 x 0,75	3084630	<input type="radio"/>	_____
			M 6 x 1	3084650	<input type="radio"/>	_____
			M 8 x 1	3084653	<input type="radio"/>	_____
			M 10 x 1	3084654	<input type="radio"/>	_____
			1/8 BSP	3084580	<input type="radio"/>	_____
			1/8 NPT	3084588	<input type="radio"/>	_____
	<b>90°</b> Ø 6 Tube	65 bar 943 psi	1/8 BSP	3084581	<input type="radio"/>	_____
			1/4 BSP	3084610	<input type="radio"/>	_____
			1/8 NPT	3084589	<input type="radio"/>	_____



**90° SWIVEL**  
Ø 4 Tube

Max Pressure	Thread	Part Number	<input type="radio"/>	_____
65 bar 943 psi	M 6 x 1	3084613	<input type="radio"/>	_____
	5/16-24 UNF	3084611	<input type="radio"/>	_____
	1/8 NPT	3084620	<input type="radio"/>	_____
	1/8 BSP	3084638	<input type="radio"/>	_____
	1/8 BSP	911096	<input type="radio"/>	_____
150 bar 2175 psi	M 8 x 1	3084731	<input type="radio"/>	_____
	1/8 BSP	3084696	<input type="radio"/>	_____



**90° SWIVEL**  
Ø 6 Tube

150 bar 2175 psi	1/8 BSP	3084695	<input type="radio"/>	_____
	1/4 BSP	308 4750	<input type="radio"/>	_____
	M 6 x 1	3084751	<input type="radio"/>	_____
	M 8 x 1	3084752	<input type="radio"/>	_____



**"T" FITTING**

Ø 4 Tube		3084641	<input type="radio"/>	_____
Ø 6 Tube		3084593	<input type="radio"/>	_____
Ø 8 Tube		3084642	<input type="radio"/>	_____
Ø 6 Tube	1/8 BSP central thread	3084564	<input type="radio"/>	_____
Ø 8 Tube	1/4 BSP Swivel central thread	3084673	<input type="radio"/>	_____
Ø 8 Tube	1/8 BSP Side thread	3084706	<input type="radio"/>	_____



**BULKHEAD**

Ø 4 Tube		3084573	<input type="radio"/>	_____
Ø 6 Tube		3084562	<input type="radio"/>	_____

## ACCESSORIES



Threaded coupling Ø 6 Tube

1/8 BSP	3084599	<input type="radio"/>	_____
---------	---------	-----------------------	-------



Plug

Ø 4 Tube	3084662	<input type="radio"/>	_____
----------	---------	-----------------------	-------



Junction tube

Ø 4 Tube	3084663	<input type="radio"/>	_____
----------	---------	-----------------------	-------



Flow regulator

Ø 6 Tube	1/8 BSP	3084621	<input type="radio"/>	_____
----------	---------	---------	-----------------------	-------