

## MK 100 Safety Data Sheet

## Safety Data Sheet MK 100 MQL oil used in minimal systems for all the alloys of good tough ability

Safety Data Sheet dated 7/9/2020 - according to EC directive 2006/8, and according to regulation (EC) no 1907/2006 (REACH), version 1

### **1.IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY**

Trade Name: MK 100 Trade Code: **3226665/3226665-M/3226691** Product type and use: Lubricant. NC: 2916.15.00

Company Name: Dropsa S.p.A. – Via B. Croce, 1 Vimodrone (MI) Tel. 02/250791 – Fax. 02/25079767

### 2.COMPOSITION / INFORMATION ON INGREDIENTS

Chemical composition : synthetic and natural ester, antioxidant, stabilyzer. Hazardous components within the meaning of EEC directive 67/548 and corresponding classification: None

#### **3.HAZARDS IDENTIFICATION**

No specific hazards are encountered under normal product use.

#### **4.FIRST-AID MEASURES**

<u>Contact with skin</u>: Wash with much water and soap, and remove dirty clothing. Call a doctor if necessary. Warning: Whenever accidents occur near pipes under pressure, there always is the possibility that the substances expelled, whatever their composition, may be injected into subcutaneous tissues, even without visible wounds appearing. When this occurs, accompany the persons affected to the nearest hospital immediately.Injuries caused by high pressure jets call for immediate surgical treatment and may require steroid- based therapy in order to minimize damage to tissues and the loss of function.

<u>Contact with eyes</u>: Keep the eyelids open and wash immediately with much water for a few minutes. If pain persists and the eyes remain red, medical care is required;

<u>Swallowing</u>: Do not induce vomit to avoid the risk of inhalation through the respiratory tract. Consult a physician.

<u>Inhalation</u>: After exposure to highly concentrated vapors and mists, remove the persons affected to a well-ventilated room. Consult a physician if ailment persists.

#### **5.FIRE-FIGHTING MEASURES**

<u>Recommended extinguishers</u>: Water, CO2, Foam, Chemical powders, according to the materials involved in the fire.

Extinguishers not to be used: None in particular.

<u>Risks arising from combustion</u>: Do not breathe combustion fumes. As a result of fire, the following compounds can develop: carbon (COx). Avoid inhaling the fumes.

Protective equipment: Use protection for the respiratory tract.





#### ubrication Systems and Solutions Specialists

Measures for personal safety: Use gloves and protective clothing.

<u>Environmental measures</u>: If the product has escaped into a water course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.

<u>Cleaning methods</u>: If the spillage has been considerable, stem the flow and scoop spilled material up into appropriate containers. Stem small spillages with dirt, sand or other inert absorbents and dispose according to relevant legislation.

#### 7.HANDLING AND STORAGE

<u>Handling precautions</u>: Avoid contact and inhalation of the vapours. See, too, paragraph 8 below. <u>Storage conditions</u>: Do not pour the product into other containers. Always use the original container.

#### **8.EXPOSURE CONTROLS / PERSONAL PROTECTION**

<u>Precautionary measures</u>: Give adequate ventilation to the premises where the product is stored and/or handled.

<u>Respiratory protection</u>: Not required in normal working conditions.

Protection for hands: Not needed for normal use.

<u>Eye protection</u>: Wear safety goggles whenever there is the possibility of a contact with the product; For additional information refer to UNI-EN 166 norm;

Protection for skin: No special precaution must be adopted for normal use.

Exposure limit(s) (ACGIH): None.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	clear liquid
Odour:	Sui generis
Boiling point:	>100 °C
Flash point:	210 ° C
Autoignition temperature:	>300 °C
Explosive properties:	not explosive
Oxidizing properties:	not oxidising
VOC content 99/13/CE:	0 %
Relative density:	0.877 Kg/l
Solubility in water:	insoluble
Viscosity 40°C ASTM D445:	11.3 cst
Viscosity 100°C ASTM D445:	3.51 cst
Viscosity index ASTM D2270:	199



# MK 100 Safety Data Sheet

ubrication Systems and Solutions Specialists

#### **10.STABILITY AND REACTIVITY**

<u>Conditions to avoid</u>: Stable under normal conditions. <u>Substances to avoid</u>: None in particular. <u>Hazardous decomposition products</u>: None.

#### **11.TOXICOLOGICAL INFORMATION**

Set out below is the toxicological information relating to the main substances in the preparation.

<u>By breathing</u>: Prolonged exposure to vapors or mists can cause irritation to the respiratory tract; <u>By swallowing</u>: The product can cause irritation in the digestive tract, with vomit, nausea and diarrhea; <u>By skin contact</u>: Prolonged and frequent contact can contribute to dryness and irritation of the skin, and may cause dermatitis;

By eye contact: Can cause a light irritation

### **12.ECOLOGICALM INFORMATION**

Adopt good working practices, so that the product is not released into the environment. The product is biodegradable at : >80 %.

Biodegredability : The product is easisly biodegradable.

List of substances dangerous for the environment and corresponding classification:

0.1% - 0.25% 3,5-Bis(1,1-dimethylethyl)-4-hydroxybenzenepropanoic acid C7-9

CAS: 125643-61-0

R53 May cause long-term adverse effects in the aquatic environment.

Acute toxicity on fishes LC50>74 mg/l OECD 203.

No effect with the highest concentration amount that has been tested

The concentration amount that has been tested is higher than its solubility in water.

Acute toxicity to daphnia (Dafnia magna 24h 20°C): EC50>100 mg/l OECD 202/ECC C 2

Acute toxicity to bacteria (Fango di figna 3h): IC50>100 mg/I OECD 209

Acute toxicity to algae (Scenedesmus sp. 72h): EC50>3 mg/l OECD 201.

No effect with the highest concentration amount that has been tested

The concentration amount that has been tested is higher than its solubility in water Biodegradability: non biodegradable OECD 301 B

### **13.DISPOSAL CONSIDERATIONS**

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Dispose of exhausted products and of containers through authorized firms.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

### **14.TRANSPORT INFORMATION**

ADR-Class: not classified.

### **15.REGULATORY INFORMATION**

Council Directive 67/548/EEC (Classification, packaging and labelling of dangerous substances) and subsequent amendments.

Commmission Directive 1999/45/EC (Classification, packaging and labelling of dangerous preparation) and subsequent

amendments. Commission Directive 98/24/EC (Protection of the health and safety of workers from the risk related to chemical

agent). Commission Directive 2000/39/EC (Occupational exposure limit values). Regulation (EC) No 1907/2006 (REACH).

The preparation should not be considered as dangerous accordingly to dir. 88/379/EEC.

Where applicable, refer to the following regulatory provisions :





#### ubrication Systems and Solutions Specialists

Regulation (EC) nr 648/2004 (Detergents).

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

#### **16.OTHER INFORMATION**

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the

European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold ACGIH - Threshold Limit Values - 2004 edition

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product

indicated and constitutes no guarantee of particular quality.

This safety data sheet has been drafted taking into account the Guidelines for the Draft of Safety Data Sheets for Lubricants

drawn up by the Gruppo Aziendale Industriali della Lubrificazione (GAIL website

http://assoscpecifici.federchimica.it/GAIL/Gail.htm) part of UEIL (Independent Union of the European Lubricants Industry)

This MSDS cancels and replaces any preceding release...

Dropsa SpA assumes no liability for any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is attributable to the gross negligence of Dropsa.